

PETRONAS VACUUM PUMP OIL 68

Special oil for high vacuum pumps

PETRONAS VACUUM PUMP OIL 68 is a highly refined mineral oil specifically designed to fulfill the needs of vacuum type applications in the refrigeration industry, for maximum efficiency of the system and corrosion prevention of the internal parts.

Applications

PETRONAS VACUUM PUMP OIL 68 is recommended for use in:

- the majority of high vacuum pumps working with an absolute pressure of 50 microns of mercury (or 0,05 torr) or even lower

Features and Benefits

Features	Benefits
Excellent viscosity retention	Fast and uniform oil distribution and perfect sealing of the narrow passages between pump blades, rotor and cylinder walls.
Very low vapor pressure	Good film strength for minimum friction and lowest possible wear.
Water separation properties	High oxidation stability for extended oil life.

Typical Properties

Characteristics	Method	68
Density @ 15°C, kg/L	ASTM D 4052	0,861
Viscosity @ 40°C, cSt	ASTM D 445	67,0
Viscosity @ 100°C, cSt	ASTM D 445	9,1
Viscosity index	ASTM D 2270	113
Flash Point, °C / °F	ASTM D 92	234 / 453
Pour Point, °C / °F	ASTM D 97	-30 / -22

All technical data are provided for reference only. SS is available upon request, including quality control limits

PETRONAS VACUUM PUMP OIL 68

Special oil for high vacuum pumps

Health, Safety and Environment

This product is unlikely to present any significant health and safety hazards when used in the recommended application. Avoid contact with skin. Wash immediately with soap and water after skin contact. Do not discharge into drains, soil or water.

For further detail regarding storage, safe handling, and disposal of product, please refer to product SDS or contact us at: www.pli-petronas.com.

Important Note

The word PETRONAS, the PETRONAS logo and such other related trademarks and/or marks used herein are trademarks or registered trademarks of PETRONAS Lubricants International Sdn. Bhd. ("PLISB"), or its subsidiaries or related Holding Corporation under license unless indicated otherwise. The PLI Documents and the information contained herein are believed to be accurate as of the date of printing. PLISB makes no express or implied representation or warranties as to its accuracy or completeness or information in or any transaction performed. The PLI Documents and information provided are based on standard tests under laboratory conditions and is given only as a guide. Users are advised to ensure that they refer to the latest version of these PLI Documents. It is the responsibility of the users to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations imposed by the respective local authorities.

Safety Data Sheets are available for all our products and should only be consulted for appropriate information regarding storage, safe handling and disposal of the product. No responsibility shall be taken by either PLISB or its subsidiaries and related holding corporation for any loss or injury or any direct, indirect, special, exemplary, consequential damages or any damages whatsoever, whether in action of contract, negligence or other tortious action, in connection with or resulting from abnormal use of the materials and/or information, from any failure to adhere to recommendations, or from hazards inherent in the nature of the materials and/or information. All products, services and information supplied are under our standard conditions of sale. Please consult with any of our local representatives in the event you require any further information.